

## Fitting Instructions for the Autolok Spigot Fold Down or Removable Security Posts


Thank you for choosing the Autolok spigot security post. Please ensure you read these instructions carefully before installing the product.

Part NO: KFP2/S, KCPS, KRP3P

### INSTALLATION

1. Please read "Important Notes" below. Choose a location for the post ensuring that the post will be free from obstructions in both the raised and lowered positions.
2. Dig the hole to a depth of 5" (127mm) deeper than the length of the ground spigot.
3. The width of the hole should be at least 12" square (304mm) allowing enough room for the post plus the filling.
4. For water drainage line the bottom of the hole with either gravel or rubble
5. Position the steel stabilising rod into the holes at the bottom of the spigot. Place the spigot into the hole so that the top of the post is at ground level.
6. Wedge the post in position and check that it is vertical, it may help to extend the post to the up-right position to check with a spirit level that the post is vertical. Now fold down or remove the post and fill with concrete.
7. Fill the rest of the hole with concrete to just below the surface plate.
8. Check that the post is still vertical, then fold down or remove the post and leave for at least 48 hours or until the concrete is fully set.

The Concrete Mix should be a strong mix (i.e. not too wet) we recommend a mix of 1 part concrete to 3 parts aggregate.



### "Important Notes" Please read carefully

When deciding the location of the post, look for drainage covers etc and avoid installation between these points to try to prevent uncovering pipes etc. Dig slowly using hand tools so that if you do encounter a pipe or cable you do not damage them. If you do encounter a pipe or cable re-fill and select a new location. If in doubt consult a qualified builder for installation of this product.

**Warning:** The Autolok Security Post is made of heavy weight steel, to prevent injury to yourself, please ensure that the post is lowered slowly into the ground.

The manufacturer reserves the right to amend the product specification at any time. This product carries a 12 month guarantee against manufacturing defects, in the unlikely event that a fault should occur, please contact our Customer Service on 0161 624 8171. The Autolok security post has been designed to act as a deterrent against theft, however theft can occur even though various security devices are fitted.

This does not effect your statutory rights