

# HIGH PERFORMANCE SILICONE LUBRICANT



## PRODUCT OVERVIEW

**WD-40® Specialist® High Performance Silicone Lubricant is a non-staining, hard working formula which provides excellent lubrication, won't attract dirt, and protects against moisture. It stops parts from sticking and can be used on high pressure equipment. This product can be used on metal, plastic, wood and rubber.**

## FEATURES AND BENEFITS

- ⊕ Dual action Smart Straw® applicator for wide area and precision spray applications
- ⊕ Excellent lubrication on plastics, rubber, wood and metal
- ⊕ Formulated for improved high pressure performance
- ⊕ Waterproofs and protects against moisture
- ⊕ Prevents rust and corrosion
- ⊕ Eliminates sticking and binding
- ⊕ Non-staining
- ⊕ Temperature range: -35°C to +200°C

**NSF H2 Registered #145374**



NARROW SPRAY



WIDE SPRAY

## TYPICAL APPLICATIONS

Belts, bearings, linkages, doors & hinges, tools, guide rails, valves, locks and hoists.

## DIRECTIONS FOR USE

Shake can well. Apply by spraying directly on surface to be lubricated and protected.

## TECHNICAL DATA

| PROPERTY                               | HIGH PERFORMANCE SILICONE LUBRICANT                        |
|--|--|
| Appearance                             | Clear yellow liquid  |
| SG                                     | 0.79 - 0.80  |
| Discharge rate                         | 0.7 - 1.2 g/s  |
| Temperature range                      | Effective performance at temperatures from -35°C to +200°C |
| Solubility                             | Not miscible with water                                    |
| NSF category                           | H2   |
| Flammability                           | Classed as extremely flammable under current legislation   |
| Compatibility                          | Metal, plastic, rubber and wood                            |
| Lubrication ASTM D-4172                | Scar depth 0.68 mm   |
| Extreme pressure lubrication ASTM 3233 | 816 lb   |

## PACKAGING SPECIFICATIONS

| PRODUCT NUMBER | UNIT SIZE | CASE SIZE  |
|----------------|-----------|------------|
| 44377          | 400ml     | 400ml x 12 |

